

Product sheet

Material: 1000001833 / 1000001835

EAN 13: 4004625413944 / 4004625409640

Manual hydraulic bender 772-773

Presentation: Wooden case Shipping Unit: 1

Image:



No.		Norma/ Norm	Radio/ Radius	kg	
2" Placa simple con tripode / Single plate tripod included					
1000001833		3/8-1/2-1-3/4-1.1/4-1.1/2-2"	DIN-2440-41	Corto/Short	63,1 1
1000001835		3/8-1/2-1-3/4-1.1/4-1.1/2-2"	DIN-2440-L	Largo/Long	69,6 1
2" Placa doble con tripode / Double plate tripod included					
1000001832		3/8-1/2-1-3/4-1.1/4-1.1/2-2"	DIN-2440-41	Corto/Short	61,3 1
1000001834		3/8-1/2-1-3/4-1.1/4-1.1/2-2"	DIN-2440-L	Largo/Long	67,7 1
3" Placa doble (sin tripode) / Double plate (tripod not included)					
1500002308		1/2-3/4-1-1.1/4-1.1/2-2-2.1/2-3"	DIN-2440-41	Largo/Long	120,0 1

No.		
Hormas radio corto / Short radius formers		
57985	3/8"	1
57986	1/2"	1
57987	3/4"	1
57988	1"	1
57989	1.1/4"	1
57990	1.1/2"	1
57991	2"	1
7M3005200	2.1/2"	1
7M3005300	3"	1
Diábolos / Pivot pipe supports		
772201200		1
772201100		1
Tripode / Tripod		
57352	2"	1
1500002988	3"	1

Certifications:

ISO 9000
ISO 14001

SUPER-EGO

Product description:

Cold bending of carbon steel and galvanised steel pipes up to 2" and 3" from 0° to 90°.

Features

- Safety valve to prevent damage in case of overload.
- Closed hydraulic system for low maintenance needs.
- Manual monoblock equipment, with automatic release.
- Reduced dimensions, compact solid construction, versatile and portable bender.
- Periodically grease the shafts and the moving parts of the bender.
- Always keep the bender clean and protected from aggressive environments.
- The volume of oil required for the 2" bender is 950 cm³ and 1,600 cm³ for the 3" bender.
- Check the oil level periodically.
- Top up the oil taking particular care in filtering it to prevent the ingress of foreign bodies.

TECHNICAL DATA

Bender: 0-90°
Capacity: 2"-3"
Application: Steel
Max. Force: 15 Tn.

Delivered in a wooden case for storage and transport, includes: hydraulic bender, short or long radius formers set, simple or double plate and pivot pipe supports

